	PRODUCT HIGHLITES				
GOLDENWOOD / GOLDENCLAD CASEMENT WINDOWS					
PRODUCT SIZE RANGE :	 WIDTH 15 3/4" (400 mm) to 35 7/16" (900 mm) - PLUS MULLED UN HEIGHT 23 5/8" (600 mm) to 76 ³/₄" (1950 mm) STANDARD CATALOGUE AND CUSTOM SIZES AVAILABLE 	ITS -2, -3 OR -4			
PICTURE WINDOWS :	 YES – STANDARD CATALOGUE and CUSTOM SIZES AVAILAL + COMBINE any OTHER SINGLE UNITS of SIMILAR HEIGHT to CASEMENT/PICTURE STYLE COMBINATIONS 				
BAY / BOW WINDOWS :	YES – STANDARD CATALOGUE and CUSTOM SIZES AVAILA + COMBINE ANY OTHER SINGLE UNITS OF SIMILAR HEIGHT 45 and 30 DEGREE ANGLE BAYS / 10 DEGREE ANGLE BOW + HEAD and / or SEAT BOARD OPTION	Г			
<u>GRILLE OPTIONS :</u>	 1" REMOVABLE WOOD PROFILED BOTH SIDES WITH FULL S 5/8" FLAT ALUMINUM BAR in WHITE, ALMOND, TAUPE, GREE and TAUPE/WHITE and 5/16" NARROW BRASS and PEWTER S WITHIN INSUL GLASS (G.B.G) – will affect energy rating ³/₄" PROFILED ALUMINUM GEORGIAN BAR IN WHITE, ALMON GREEN, SABLE and TAUPE/WHITE WITHIN INSUL GLASS (G affect energy rating 1" SIMULATED DIVIDED LITES (SDL) – ALUMINUM ON ALL EX WOOD INTERIORS. (will affect energy rating) 	PROFILED ALUMINUM GEORGIAN BAR IN WHITE, ALMOND, TAUPE, EEN, SABLE and TAUPE/WHITE WITHIN INSUL GLASS (G.B.G) – will ct energy rating IMULATED DIVIDED LITES (SDL) – ALUMINUM ON ALL EXTERIORS –			
<u>GLAZING OPTIONS :</u>	 STANDARD INSUL UNIT CONSISITS of 2 pcs CLEAR 3mm GL/ WARM EDGE SPACER TECHNOLOGY (Choice of Standard "In Upgrade to "SuperSpacer") OR BRONZE or GREYLITE REPLACES OUTSIDE LITE OF GLA 	ntercept" or			

- OR BRONZE or GREYLITE REPLACES OUTSIDE LITE OF GLASS OR GOLDENGLASS (highly recommended) WITH "LOW E" HARD
- COATING ON INSIDE LITE OF GLASS (#3 surface) + ARGON GAS EN -HANCED AIR SPACE (grilles between glass and SDL will affect energy rating) TEMPERED and OBSCURE OPTIONS ALSO AVAILABLE
- GOLDENWOOD NATURAL PINE FINGER JOINT EXTERIOR WOOD OR **EXTERIOR FINISHES** :
 - GOLDENCLAD ALUMINUM CLAD EXTERIOR IN 6 COLOURS :
- S SABLE A - ALMOND G - GREEN T - TAUPE W - WHITE C - CRANBERRY (OPTIONAL) ALL WOOD – CLEAR PINE VENEER FINISH **INTERIOR FINISHES :** COPPERTONE or WHITE HARDWARE and SCREEN (SPECIFY COLOUR) And HARDWARE TRUTH " MAXIM " ROTO OPERATOR on VENTING UNITS MULTI POINT SINGLE LEVER LOCKING SYSTEM GOLDENWOOD – STANDARD JAMB WIDTH 4 9/16" JAMB EXTENSIONS : GOLDENCLAD – OVERALL JAMB 5 11/16" (NAIL FIN OPTION) YES – UP TO 2" INSTALLED CHOICE OF CLEAR PINE (FOR STAIN) or FINGER JOINT (FOR PAINT)
- FEATURES & DETAILS : REFER TO LITERATURE / BROCHURES
- **OPERATION**:
- SIDE HINGED SWINGING OUTWARD HINGING ALWAYS AS VIEWED FROM EXTERIOR – GENERALLY OUTSIDE LEFT SECTIONS ARE LEFT HINGED (L) AND RIGHT PANELS RIGHT HINGED (R) – CENTRE AREA PANELS ARE CUSTOMER CHOICE
 - EXAMPLE : WC0616-4 WITH 2 VENTS (ie : WC0616-4 LFFR) LEFT HINGED (L), 2 FIXED CENTRE PANELS (FF), RIGHT HINGED (R)

GOLDENWOOD[®] & GOLDENCLAD[®] SPECIFICATIONS & CONSTRUCTION DETAILS

COMPONENT	SPECIFICATIONS	Csaement	Awning	Double Hung	Decorative Products	Direct Set
FRAME	Select kiln-dried pine - solid, clear and preservative treated. Precision smooth knife finish. Jamb width 4 9/16". Curved components of laminated veneers (clear interior veneers).	•	•	•	•	•
FRAME CLADDING	Commercial gauge extruded aluminum with baked Duracron or Macroflex finish - #K1285 White, #K72191 Sable, #K30333 Almond, #UC30930 Taupe, #UC98690 Green and #UC98857 Cranberry.		•	•	•	•
SASH	Select kiln-dried pine - solid, clear and preservative treated. Precision smooth knife finish. Glued mortise and tenon construction.		•	•	No Sash	No Sash
SASH CLADDING	Commercial gauge extruded aluminum in matching frame colours.		•	•	No Sash	No Sash
GLAZING	2 pieces of 3 mm (minimum) float glass with 1/2" air space creates an overall 3/4" insulating glass unit. Warm edge spacer technology. Double Hung sash are clamp glazed with setting blocks - butyl heel bead on glass to wood components and silicone glass to cladding application. Decorative, Casement, Awning and Direct Set products interior stop glazed with exterior heel bead.	•	•	•	• No Sash	• No Sash •
HARDWARE	Concealed stainless steel hinges with stainless steel reinforced nylon (Delrin) slide shoe. Heavy gauge steel support arms with E-Gard [™] multi-layer coating to resist corrosion. Heavy gauge steel hinge track and support arms with stainless steel reinforced acetal slide shoe. E-Gard [™] multi-layer coating to resist corrosion. Truth Maxim [™] operator with E-Gard [™] coating on arms. Dyad operator to 650 mm (25 ¹⁹ /32 [°])width, dual arm 651 mm (25 ⁵ /8") to 900 mm (35 ⁷ /16") widths. Zinc die-cast operator and hardened steel drive worm and gear. Integral metal cover. Coppertone or white colour available. Truth Maxim [™] roto awning operator. Steel base plate and lever arms with E-Gard [™] multi-layer coating to resist corrosion. Coppertone or white colour available. Mirage [®] die-cast zinc bezel and locking handle. E-Gard [™] keeper and steel locking mechanism - 5/8" reach. Coppertone or white colour available. Block and tackle balance system with tilt and take-out features. Reinforced nylon positive locking shoe. Rust resistant balances and accessories. Injection moulded tilt release latches. Cam action lock with push-button security feature. Powder coated finish in almond or white colour to match liner and tilt release latches.	•	•	•		
SCREENS	Heavy roll formed aluminum frame bar with 18 x 16 mesh charcoal fibreglass screen cloth. Easy to remove.	•	•	•	No Vent	No Vent
WEATHERSTRIPPING	Replaceable cellular modified foam core, wrapped in U.V. stabilized paint- resistant liner. Maintains compression flexibility in wide temperature range.	•	•	•		
OPTIONS						
GLAZING	GoldenGlass [®] High performance glazing - Low E and Argon Gas enhanced. Includes warm edge spacer technology.	•	•	•	•	•
GRILLES	 Colonial , Victorian or Muskokan patterns: Grilles between glass (G.B.G.): 5/8" Flat Aluminum - White, Almond, Taupe, Sable, Green, and split finish (Taupe/White); 5/16" Flat Narrow Aluminum - Pewter and Brass; 3/4" "Georgian" Profiled Aluminum - White, Almond, Taupe, Sable, Green, and split finish (Taupe/White); 1" Profiles Wood Removable c/w Full Wood Surround (not available in Muskokan pattern). 1" Simulated Divided Lite (SDL) - Profiled Aluminum Exterior and Wood Interior - White, Almond, Taupe, Sable, Green and Cranberry. 2" Simulated Horizontal Mullion to simulate Vertical Hung window style. Aluminum Exterior/Wood Interior - White, Almond, Taupe, Sable, Green and Cranberry. 	• • • • •	• • • • •	• • • • •	• • •	• • • •
JAMB EXTENSIONS	2" Pine - Clear (up to $76^3/4$ " or 1950mm) or finger joint.	•	•	•	•	•
BRICK MOULD	Extruded aluminum in matching colours (not available for curved shapes). NOTE: We reserve the right to change specifications in the interest of product improvement.	•	•	•		•