

## GOLDENCLAD® & GOLDENWOOD® AWNING WINDOW PRODUCT HIGHLIGHTS

• WIDTH 31-1/2" (800 mm) to 55-1/8" (1400 mm) - PLUS MULLED UNITS (UP TO 5)

• HEIGHT 19-11/16" (500 mm) to 47-1/4" (1200 mm) - OR STACK UNITS

STANDARD CATALOGUE AND CUSTOM SIZES AVAILABLE

PICTURE WINDOWS: • YES - STANDARD CATALOGUE AND CUSTOM SIZES AVAILABLE

+ COMBINE ANY OTHER SINGLE UNIT OF SAME HEIGHT TO CREATE AWNING/

PICTURE STYLE COMBINATIONS

**BAY/BOW WINDOWS:** • NO

GRILLE OPTIONS: COLONIAL, MUSKOKA, VICTORIAN, HORIZONTAL, CUSTOM PATTERNS AVAILABLE

**GRILLES BETWEEN GLASS - INTERNAL (GBG):** 

• 5/8" FLAT ALUMINUM BAR - WHITE, TAUPE, SABLE, BLACK, AND SPLIT FINISH

• 5/16" FLAT NARROW ALUMINUM BAR - PEWTER AND BRASS

• 3/4" GEORGIAN PROFILED ALUMINUM BAR - WHITE, TAUPE, SABLE, BLACK AND

SPLIT FINISH

WILL AFFECT ENERGY RATING

SIMULATED DIVIDED LITE - EXTERNAL (SDL):

1" SIMULATED DIVIDED LITE (SDL) - ALUMINUM EXTERIOR - WOOD INTERIOR
2" SIMULATED HORIZONTAL MULLION - ALUMINUM EXTERIOR - WOOD INTERIOR

• WILL AFFECT ENERGY RATING

**GLAZING OPTIONS:** • STANDARD INSUL UNIT CONSISTS OF DUAL GLAZED 1 PC CLEAR GLASS AND 1 PC

LOW-E GLASS WITH 1/2" WARM EDGE SPACER TECHNOLOGY + ARGON GAS

ENHANCED AIR SPACE

TRIPLE GLAZE UNIT AVAILABLE WITH VARIOUS LOW-E COATING CONFIGURATIONS

• BRONZE OR GREY LITE REPLACES OUTSIDE LITE OF GLASS

• VARIOUS OPTIONS FOR LOW-E COATINGS AVAILABLE TO ACHIEVE DIFFERENT

LEVELS OF ENERGY PERFORMANCE

TEMPERED AND OBSCURE OPTIONS ALSO AVAILABLE

• STANDARD INTERCEPT OR UPGRADE TO SUPERSPACER

**EXTERIOR FINISHES:**• GOLDENWOOD - NATURAL PINE, PERESERVATIVE TREATED - FINGER JOINT

EXTERIOR WOOD OR/

• GOLDENCLAD - ALUMINUM CLAD EXTERIOR IN 4 STANDARD COLOURS AND/OR

OPTIONAL/CUSTOM COLOURS

• EXTERIOR PRIMING OPTION AVAILABLE

CUSTOM WOOD SPECIES AVAILABLE

INTERIOR FINISHES:

& HARDWARE

• ALL WOOD - FINGER JOINT PINE FINISH, CLEAR PINE AND CUSTOM WOOD SPECIES

AVAILABLE

• 3 SCREEN COLOURS AND 6 HARDWARE COLOURS AVAILABLE

TRUTH-AMESBURY "ENCORE" OPERATOR ON VENTING UNITS

MULTIPOINT SINGLE LEVER LOCKING SYSTEM

JAMB EXTENSIONS: • GOLDENWOOD - STANDARD JAMB WIDTH 4-9/16"

• GOLDENCLAD - OVERALL JAMB 5-11/16", 4-9/16" BEHIND NAILING FIN

• 2" JE STANDARD OPTION OR CUSTOM JAMB DEPTHS AVAILABLE

• CHOICE OF CLEAR PINE (FOR STAIN) OR FINGER JOINT (FOR PAINT)

FEATURES & DETAILS • REFER TO BROCHURE

**OPERATION:** • TOP HINGED SWINGING OUTWARD

• WHEN STACKING UNITS, LOWER SECTIONS GENERALLY ARE USED FOR

VENTILATION AND TOP SECTIONS ARE FIXED. HOWEVER, MOST TOP SECTIONS CAN ALSO BE VENTED IF REQUESTED. REFER TO BROCHURE FOR VENTING SIZE OPTIONS.