

## GOLDENCLAD® & GOLDENWOOD® ENTRY SYSTEM PRODUCT HIGHLIGHTS

### PRODUCT SIZE RANGE:

- SINGLE, SINGLE WITH SIDELITE(S), DOUBLE DOOR AND/OR DOUBLE DOOR WITH SIDELITE(S)
- WIDTHS AVAILABLE FROM: 31 1/2" (800MM) TO 105-3/4" (2686MM)
- STANDARD HEIGHT
  - 6'-8" DOORS: 81-9/16" (2072MM)
  - 7'-0" DOORS: 85-9/16" (2174MM)
  - 8'-0" DOORS: 97-9/16" (2478MM)
- OTHER CUSTOM SIZES AVAILABLE

### SIDELITES:

- 0'-8", 1'-0", AND 1'-2" STANDARD SIDELITE SLAB WIDTHS, CUSTOM SIZES AVAILABLE
- FIBERGLASS OR STEEL SIDELITE SLABS WITH OR WITHOUT INSERTS, KICK PANEL SIDELITES AND ALL GLASS SIDELITES AVAILABLE

### DOOR PANELS:

- STEEL OR FIBERGLASS SLABS IN VARIOUS STYLES, WITH OR WITHOUT GLASS INSERTS, OR ALUMINUM CLAD PINE INTERIOR SLABS WITH FULL-LITE GLASS INSERTS
- 2'-4" UP TO 3'-6" SLAB WIDTHS
- 6'-8", 7'-0" OR 8'-0" SLAB HEIGHTS

### STANDARD GLAZING:

- STANDARD LOW-E INSULATING GLASS IN HALF LITES AND SIDELITES
- TEMPERED LOW-E INSULATING GLASS IN 3/4" & FULL LENGTHS LITES
- DOOR LITE SURROUNDS AVAILABLE IN WHITE (WILL NOT YELLOW) OR STAINABLE FINISHES
- OBSCURE, BRONZE, OR GREY LITE AVAILABLE AS AN OPTION
- MANY STYLES OF DECORATIVE DOOR AND SIDELITE INSERTS AVAILABLE

### GRILLE OPTIONS:

#### COLONIAL, MUSKOKA, VICTORIAN, HORIZONTAL, CUSTOM PATTERNS AVAILABLE

##### GRILLES BETWEEN GLASS - INTERNAL (GBG):

- 5/8" FLAT ALUMINUM BAR - WHITE, TAUPE, SABLE, BLACK, AND SPLIT FINISH
- 5/16" FLAT NARROW ALUMINUM BAR - PEWTER AND BRASS
- 3/4" GEORGIAN PROFILED ALUMINUM BAR - WHITE, TAUPE, SABLE, BLACK AND SPLIT FINISH
- GBG WILL AFFECT ENERGY RATING

##### SIMULATED DIVIDED LITE - EXTERNAL (SDL):

- 1" SIMULATED DIVIDED LITE (SDL) - ALUMINUM EXTERIOR - WOOD INTERIOR
- 2" SIMULATED HORIZONTAL MULLION - ALUMINUM EXTERIOR - WOOD INTERIOR

### EXTERIOR FINISHES:

- GOLDENWOOD - NATURAL PINE, PRESERVATIVE TREATED - FINGER JOINT EXTERIOR WOOD OR/
- GOLDENCLAD - EXTERIOR IN 4 STANDARD COLOURS (WHITE, BLACK, SABLE, TAUPE) AND/OR OPTIONAL/CUSTOM COLOURS
- EXTERIOR PRIMING OPTION AVAILABLE
- CUSTOM WOOD SPECIES AVAILABLE

### JAMB EXTENSIONS:

- GOLDENWOOD - STANDARD JAMB WIDTH 4-9/16"
- GOLDENCLAD - OVERALL JAMB 5-11/16", 4-9/16" BEHIND NAILING FIN, 6-9/16", 7-1/16" AND 7-9/16" JAMB DEPTH OPTIONS AVAILABLE - INCLUDES SILL EXTENSION

### FEATURES & DETAILS:

- REFER TO LITERATURE/BROCHURE

### OPERATION:

- HINGED LEFT (L) OR RIGHT (R) AS VIEWED FROM OUTSIDE
- OUT SWING OPTION IN SINGLE DOOR ONLY
- NO OUT SWING OPTION FOR DOUBLE DOORS

### HARDWARE PREP:

- DRILLED 2-1/8" AND DEADBOLT 1-5/8" ON 5-1/2" CENTRE - SINGLE DOORS
- DRILLED 2-1/8" AND DEADBOLT 1-5/8" ON 5-1/2" CENTRE ON ACTIVE DOOR AND 2-1/8" FOR DUMMY SET ON INACTIVE DOOR SLAB - DOUBLE DOORS
- BACK SET 2'-6" AND 2'-8" DOORS - 2-3/8"
- BACK SET 2'-10" AND 3'-0" DOORS - 2-3/4"
- JAMB PREPARED FOR STRIKE PLATE
- 2-1/8" DEADBOLT OR NO DEADBOLT DRILL AVAILABLE AS AN OPTION
- MULTI-POINT LOCKING HARDWARE WITH LEVER OR GRIPSET HANDLES AVAILABLE