

## GOLDENCLAD® & GOLDENWOOD® TERRACE PATIO ENTRY PRODUCT HIGHLIGHTS

### PRODUCT SIZE RANGE:

- TWO PANEL DOOR WIDTHS: 62-13/16" (1596MM) TO 74-13/16" (1901MM)
- THREE PANEL DOOR WIDTHS: 94-3/16" (2392MM) TO 112-3/16" (2849MM)
- FOUR PANEL DOOR WIDTHS: 125-1/2" (3188MM) TO 141-1/2" (3594MM)
- STANDARD HEIGHTS:
  - 6'-8" DOORS: 81-9/16" (2072MM)
  - 7'-0" DOORS: 85-9/16" (2174MM)
  - 8'-0" DOORS: 97-9/16" (2478MM)

### STANDARD GLAZING:

- TEMPERED LOW-E INSULATING GLASS IN 3/4" & FULL LENGTH LITES
- DOOR LITE SURROUNDS AVAILABLE IN WHITE (WILL NOT YELLOW) OR STAINABLE FINISHES
- OBSCURE, BRONZE OR GREY LITE AVAILABLE AS AN OPTION
- MANY STYLES OF DECORATIVE DOOR AND SIDELITE INSERTS AVAILABLE

### GRILLE OPTIONS:

**COLONIAL, MUSKOKA, VICTORIAN, HORIZONTAL, CUSTOM PATTERNS AVAILABLE**

#### **GRILLES BETWEEN GLASS - INTERNAL (GBG):**

- 5/8" FLAT ALUMINUM BAR - WHITE, TAUPE, SABLE, BLACK, AND SPLIT FINISH
- 5/16" FLAT NARROW ALUMINUM BAR - PEWTER AND BRASS
- 3/4" GEORGIAN PROFILED ALUMINUM BAR - WHITE, TAUPE, SABLE, BLACK AND SPLIT FINISH
- GBG WILL AFFECT ENERGY RATING

#### **SIMULATED DIVIDED LITE - EXTERNAL (SDL):**

- 1" SIMULATED DIVIDED LITE (SDL) - ALUMINUM EXTERIOR - WOOD INTERIOR
- 2" SIMULATED HORIZONTAL MULLION - ALUMINUM EXTERIOR - WOOD INTERIOR

### EXTERIOR FINISHES:

- GOLDENWOOD - NATURAL PINE, PRESERVATIVE TREATED - FINGER JOINT EXTERIOR WOOD OR/
- GOLDENCLAD - EXTERIOR IN 4 STANDARD COLOURS (WHITE, BLACK, SABLE, TAUPE) AND/OR OPTIONAL/CUSTOM COLOURS
- EXTERIOR PRIMING OPTION AVAILABLE
- CUSTOM WOOD SPECIES AVAILABLE

### DOOR PANELS:

- STEEL OR FIBERGLASS SLABS AVAILABLE IN VARIOUS STYLES, WITH OR WITHOUT GLASS INSERTS, OR ALUMINUM CLAD PINE INTERIOR SLABS WITH FULL-LITE GLASS INSERTS
- 2'-8" UP TO 3'-6" SLAB WIDTHS, AND 6'-8", 7'-0", OR 8'-0" SLAB HEIGHTS

### SCREEN FINISHES:

- WHITE ON WHITE CLAD (OR ON WOOD EXTERIOR), MATCHING TAUPE, SABLE AND BLACK ON CLAD EXTERIORS OR CUSTOM COLOURS

### JAMB EXTENSIONS:

- GOLDENWOOD - STANDARD JAMB WIDTH 4-9/16"
- GOLDENCLAD - OVERALL JAMB 5-11/16", 4-9/16" BEHIND NAILING FIN, 6-9/16", 7-1/16" AND 7-9/16" JAMB DEPTH OPTIONS AVAILABLE - INCLUDES SILL EXTENSION

### FEATURES & DETAILS:

- REFER TO LITERATURE/BROCHURE

### OPERATION:

- SWINGING INWARD ONLY
- OPERATION AS VIEWED FROM OUTSIDE
- EXAMPLE: 2 WIDE DOOR WITH LEFT DOOR SWINGING INWARD, HINGED ON THE MULLION - CODE IS "RF" - RIGHT HINGED LEFT PANEL, FIXED RIGHT PANEL
- IF HINGED ON JAMB, CODE IS "LF" - LEFT HINGED LEFT PANEL, FIXED RIGHT PANEL

### HARDWARE PREP:

- DRILLED 2-1/8" AND DEADBOLT 1-5/8" ON 5-1/2" CENTRE - SINGLE DOORS
- DRILLED 2-1/8" AND DEADBOLT 1-5/8" ON 5-1/2" CENTRE ON ACTIVE DOOR AND 2-1/8" FOR DUMMY SET ON INACTIVE DOOR SLAB - DOUBLE DOORS
- BACK SET 2'-6" AND 2'-8" DOORS - 2-3/8"
- BACK SET 2'-10" AND 3'-0" DOORS - 2-3/4"
- JAMB PREPARED FOR STRIKE PLATE
- 2-1/8" DEADBOLT OR NO DEADBOLT DRILL AVAILABLE AS AN OPTION
- MULTI-POINT LOCKING HARDWARE WITH LEVER OR GRIPSET HANDLES AVAILABLE