

## GOLDENVINYL® 1000 SERIES AWNING WINDOW PRODUCT HIGHLIGHTS

**PRODUCT SIZE RANGE:**

- WIDTH 18-11/16" (475 mm) to 55-1/8" (1400 mm) - PLUS MULLED UNITS (UP TO 5)
- HEIGHT 15-3/4" (400 mm) to 47-1/4" (1200 mm) - OR STACK UNITS
- STANDARD CATALOGUE AND CUSTOM SIZES AVAILABLE

**PICTURE WINDOWS:**

- YES - STANDARD CATALOGUE AND CUSTOM SIZES AVAILABLE
- FIXED SASH CONFIGURATIONS AVAILABLE IN LARGER SIZES
- + COMBINE ANY OTHER SINGLE UNIT OF SAME HEIGHT TO CREATE AWNING/PICTURE STYLE COMBINATIONS

**BAY/BOW WINDOWS:**

- NO

**GRILLE OPTIONS:**

**COLONIAL, MUSKOKA, VICTORIAN, HORIZONTAL, CUSTOM PATTERNS AVAILABLE**

**GRILLES BETWEEN GLASS - INTERNAL (GBG):**

- 5/8" FLAT ALUMINUM BAR - WHITE, TAUPE, SABLE, BLACK, AND SPLIT FINISH
- 5/16" FLAT NARROW ALUMINUM BAR - PEWTER AND BRASS
- 3/4" GEORGIAN PROFILED ALUMINUM BAR - WHITE, TAUPE, SABLE, BLACK AND SPLIT FINISH
- WILL AFFECT ENERGY RATING

**SIMULATED DIVIDED LITE - EXTERNAL (SDL):**

- 1" SIMULATED DIVIDED LITE (SDL) - ALUMINUM EXTERIOR - WOOD INTERIOR
- 2" SIMULATED HORIZONTAL MULLION - ALUMINUM EXTERIOR - WOOD INTERIOR
- WILL AFFECT ENERGY RATING

**GLAZING OPTIONS:**

- STANDARD INSUL UNIT CONSISTS OF DUAL GLAZED 1 PC CLEAR GLASS AND 1 PC LOW-E GLASS WITH 1/2" WARM EDGE SPACER TECHNOLOGY + ARGON GAS ENHANCED AIR SPACE
- TRIPLE GLAZE UNIT AVAILABLE WITH VARIOUS LOW-E COATING CONFIGURATIONS
- OR BRONZE OR GREY LITE REPLACES OUTSIDE LITE OF GLASS
- VARIOUS OPTIONS FOR LOW-E COATINGS AVAILABLE TO ACHIEVE DIFFERENT LEVELS OF ENERGY PERFORMANCE
- TEMPERED AND OBSCURE OPTIONS ALSO AVAILABLE
- STANDARD INTERCEPT OR UPGRADE TO SUPERSPACER

**EXTERIOR FINISHES:**

- LOW MAINTENANCE AND DURABLE EXTRUDED PVC FRAMES
- UV TOUGH COAT FOR STANDARD OPTIONAL COLOURS: BLACK, TAUPE, SABLE
- OPTIONAL/CUSTOM PAINTED COLOURS ALSO AVAILABLE

**INTERIOR FINISHES: & HARDWARE**

- STANDARD WHITE VINYL INTERIOR FINISH
- PAINTED INTERIOR COLOURS ALSO AVAILABLE
- MATCHING SCREEN COLOURS AVAILABLE
- STANDARD CRANK HANDLE OPERATOR ON VENTING UNITS
- OPTIONAL FOLDABLE HANDLE OPERATOR AVAILABLE IN BLACK OR WHITE

**JAMB EXTENSIONS:**

- STANDARD JAMB DEPTH 4-5/8" (3-1/2" BEHIND NAILING FIN)
- JAMB DEPTHS UP TO 9-9/16" BEHIND NAILING FIN OPTIONS OR CUSTOM JAMB DEPTHS AVAILABLE
- CHOICE OF PRIMED, CLEAR, OR CELLULAR PVC MATERIAL

**FEATURES & DETAILS**

- REFER TO BROCHURE

**OPERATION:**

- TOP HINGED SWINGING OUTWARD
- WHEN STACKING UNITS, LOWER SECTIONS GENERALLY ARE USED FOR VENTILATION AND TOP SECTIONS ARE FIXED. HOWEVER, MOST TOP SECTIONS CAN ALSO BE VENTED IF REQUESTED. REFER TO BROCHURE FOR VENTING SIZE OPTIONS.