

GOLDENVINYL® 1000 SERIES CASEMENT WINDOW PRODUCT HIGHLIGHTS

PRODUCT SIZE RANGE:

- WIDTH 15-3/4" (400 mm) to 35-7/16" (900 mm) - PLUS MULLED UNITS (UP TO 5)
- HEIGHT 19-11/16" (500 mm) to 76-3/4" (1950 mm) - OR STACK UNITS
- STANDARD CATALOGUE AND CUSTOM SIZES AVAILABLE

PICTURE WINDOWS:

- YES - STANDARD CATALOGUE AND CUSTOM SIZES AVAILABLE
- FIXED SASH CONFIGURATIONS AVAILABLE IN LARGER SIZES
- + COMBINE ANY OTHER SINGLE UNIT OF SAME HEIGHT TO CREATE CASEMENT/PICTURE STYLE COMBINATIONS

BAY/BOW WINDOWS:

- YES - STANDARD CATALOGUE AND CUSTOM SIZES AVAILABLE + COMBINE ANY OTHER SINGLE UNITS OF SAME HEIGHT
- 45 AND 30 DEGREE ANGLE BAYS / 10 DEGREE ANGLE BOWS + HEAD AND/OR SEAT BOARD OPTION

GRILLE OPTIONS: **COLONIAL, MUSKOKA, VICTORIAN, HORIZONTAL, CUSTOM PATTERNS AVAILABLE**

GRILLES BETWEEN GLASS - INTERNAL (GBG):

- 5/8" FLAT ALUMINUM BAR - WHITE, TAUPE, SABLE, BLACK, AND SPLIT FINISH
- 5/16" FLAT NARROW ALUMINUM BAR - PEWTER AND BRASS
- 3/4" GEORGIAN PROFILED ALUMINUM BAR - WHITE, TAUPE, SABLE, BLACK AND SPLIT FINISH
- WILL AFFECT ENERGY RATING

SIMULATED DIVIDED LITE - EXTERNAL (SDL):

- 1" SIMULATED DIVIDED LITE (SDL) - ALUMINUM EXTERIOR - WOOD INTERIOR
- 2" SIMULATED HORIZONTAL MULLION - ALUMINUM EXTERIOR - WOOD INTERIOR
- WILL AFFECT ENERGY RATING

GLAZING OPTIONS:

- STANDARD INSUL UNIT CONSISTS OF DUAL GLAZED 1 PC CLEAR GLASS AND 1 PC LOW-E GLASS WITH 1/2" WARM EDGE SPACER TECHNOLOGY + ARGON GAS ENHANCED AIR SPACE
- TRIPLE GLAZE UNIT AVAILABLE WITH VARIOUS LOW-E COATING CONFIGURATIONS
- OR BRONZE OR GREY LITE REPLACES OUTSIDE LITE OF GLASS
- VARIOUS OPTIONS FOR LOW-E COATINGS AVAILABLE TO ACHIEVE DIFFERENT LEVELS OF ENERGY PERFORMANCE
- TEMPERED AND OBSCURE OPTIONS ALSO AVAILABLE
- STANDARD INTERCEPT OR UPGRADE TO SUPERSPACER

EXTERIOR FINISHES:

- LOW MAINTENANCE AND DURABLE EXTRUDED PVC FRAMES
- UV TOUGH COAT FOR STANDARD OPTIONAL COLOURS: BLACK, TAUPE, SABLE
- OPTIONAL/CUSTOM PAINTED COLOURS ALSO AVAILABLE

INTERIOR FINISHES: & HARDWARE

- STANDARD WHITE VINYL INTERIOR FINISH
- PAINTED INTERIOR COLOURS ALSO AVAILABLE
- MATCHING SCREEN COLOURS AVAILABLE
- STANDARD CRANK HANDLE OPERATOR ON VENTING UNITS
- OPTIONAL FOLDABLE HANDLE OPERATOR AVAILABLE IN BLACK OR WHITE

JAMB EXTENSIONS:

- STANDARD JAMB DEPTH 4-5/8" (3-1/2" BEHIND NAILING FIN)
- JAMB DEPTHS UP TO 9-9/16" BEHIND NAILING FIN OPTIONS OR CUSTOM JAMB DEPTHS AVAILABLE
- CHOICE OF PRIMED, CLEAR, OR CELLULAR PVC MATERIAL

FEATURES & DETAILS

- REFER TO BROCHURE

OPERATION:

- SIDE HINGED SWINGING OUTWARD - HINGING ALWAYS AS VIEWED FROM EXTERIOR - GENERALLY OUTSIDE LEFT SECTIONS OF COMBINED UNITS ARE LEFT HINGED (L) AND RIGHT SECTIONS ARE RIGHT HINGED (R) - CENTRE AREA PANELS ARE CUSTOMER CHOICE
- EXAMPLE: PC0616-4 WITH 2 VENTS (OPERATION = LFFR)
 - LEFT HINGED (L)
 - 2 FIXED CENTRE PANELS (FF)
 - RIGHT HINGED (R)