

GOLDENCLAD® & GOLDENWOOD® AWNING WINDOW PRODUCT HIGHLIGHTS

- PRODUCT SIZE RANGE:**
- WIDTH 20 5/8" (525 mm) to 47 1/4" (1200 mm) - PLUS MULLED UNITS -2 OR -3
 - HEIGHT 15 3/4" (400 mm) to 39 3/8" (1000 mm) - OR STACK UNITS
 - STANDARD CATALOGUE AND CUSTOM SIZES AVAILABLE
- PICTURE WINDOWS:**
- YES - STANDARD CATALOGUE AND CUSTOM SIZES AVAILABLE
 - + COMBINE ANY OTHER SINGLE UNIT OR SIMILAR HEIGHT TO CREATE AWNING/ PICTURE STYLE COMBINATIONS
- BAY/BOW WINDOWS:**
- NO
- GRILLE OPTIONS:**
- COLONIAL OR VICTORIAN PATTERNS AVIALABLE IN:
 - 1" REMOVABLE WOOD PROFILED BOTH SIDES WITH FULL SURROUND
 - 5/8" FLAT ALUMINUM BAR IN WHITE, ALMOND, TAUPE, GREEN, SABLE AND TAUPE/ WHITE
 - 5/16" NARROW BRASS AND PEWTER SEALED
 - GRILLES BETWEEN THE GLASS (GBG) WILL AFFECT ENERGY RATING
 - 3/4" PROFILED ALUMINUM GEORGIAN BAR IN WHITE, ALMOND, TAUPE, GREEN, SABLE AND TAUPE/WHITE WITHIN INSUL GLASS (GBG) - WILL AFFECT ENERGY RATING
 - 1" SIMULATED DIVIDED LITES (SDL) - ALUMINUM ON ALL EXTERIORS - WOOD I INTERIORS - WILL AFFECT ENERGY RATINGS
- GLAZING OPTIONS:**
- STANDARD INSUL UNIT CONSISTS OF 2 PCS CLEAR 3MM GLASS WITH 1/2" WARM EDGE SPACER TECHNOLOGY (CHOICE OF STANDARD INTERCEPT OR UPGRADE TO SUPERSPACER)
 - OR BRONZE OR GREY LITE REPLACES OUTSIDE LITE OF GLASS
 - OR GOLDENGLASS (HIGHLY RECOMMEND) WITH LOW E HARD COATING ON INSIDE LITE OF GLASS (#3 SURFACE) + ARGON GAS ENHANCED AIR SPACE (GRILLES BETWEEN GLASS AND SDL WILL AFFECT ENERGY RATING)
 - TEMPERED AND OBSCURE OPTIONS ALSO AVAILABLE
- EXTERIOR FINISHES:**
- GOLDENWOOD - NATURAL PINE - FINGER JOINT EXTERIOR WOOD OR/
 - GOLDENCLAD - ALUMINUM CLAD EXTERIOR IN 6 COLOURS:
 - WHITE, BLACK, TAUPE, SABLE, GREEN, CRANBERRY (OPTIONAL)
- INTERIOR FINISHES:
& HARDWARE**
- ALL WOOD - CLEAR PINE VENEER FINISH
 - COPPERTONE OR WHITE HARDWARE AND SCREEN (SPECIFY COLOUR)
 - TRUTH "MAXIM" ROTO OPERATOR ON VENTING UNITS
- JAMB EXTENSIONS:**
- GOLDENWOOD - STANDARD JAMB WIDTH 4-9/16"
 - GOLDENCLAD - OVERALL JAMB 5-11/16" (NAIL FIN OPTION)
 - YES - UP TO 2" INSTALLED
 - CHOICE OF CLEAR PINE (FOR STAIN) OR FINGER JOINT (FOR PAINT)
- FEATURES & DETAILS**
- REFER TO BROCHURE
- OPERATION:**
- TOP HINGED SWINGING OUTWARD
 - WHEN STACKING UNITS, LOWER SECTIONS GENERALLY ARE USED FOR VENTILATION AND TOP SECTIONS ARE FIXED. HOWEVER, MOST TOP SECTIONS CAN ALSO BE VENTED IF REQUESTED. REFER TO BROCHURE FOR VENTING SIZE OPTIONS.