

## **GOLDENCLAD® & GOLDENWOOD® ENTRY SYSTEM PRODUCT HIGHLIGHTS**

- PRODUCT SIZE RANGE:**
- SINGLE, SINGLE WITH SIDELITE(S) & DOUBLE DOOR
  - WIDTH 33 1/2" TO 74"
  - STANDARD HEIGHT 81 1/2" OR 97 1/2" HEIGHT OPTIONAL
  - OTHER CUSTOM SIZES AVAILABLE
- SIDELITES:**
- YES - 9 3/4" (NSL) OR 15 1/2" (SL) FRAME WIDTH - REFER TO LITERATURE
- DOOR PANELS:**
- HEAVY 24 GAUGE STEEL (NOT 26 OR 28 GAUGE) WITH FOAMED URETHANE CORE (R13 VALUE) - 1 3/4" THICK
- STANDARD GLAZING:**
- STANDARD CLEAR INSULATING GLASS IN HALF LITES AND SIDELITES
  - TEMPERED CLEAR INSULATING GLASS IN 3/4" & FULL LENGTH LITES
  - POLYPROPYLENE VINYL EXTERIOR AND INTERIOR DOOR LITE SURROUND - CAN EITHER BE PAINTED OR LEFT WHITE (WILL NOT YELLOW)
  - GOLDENGLASS (LOW E/ARGON GAS), OBSCURE, BRONZE OR GREY LITE AVAILABLE AS AN OPTION
- GRILLE OPTIONS:**
- COLONIAL, VICTORIAN, MUSKOKA OR CUSTOM (SDL & GBG ONLY) PATTERNS
  - AVAILABLE WITH: 5/8" OR 5/16" INTERNAL FLAT ALUMINUM GRILLE BAR (GBG), 3/4" PROFILED ALUMINUM GEORGIAN GRILLE BAR (GBG) OR 1" SIMULATED DIVIDED LITE (SDL) - ASK FOR DETAILS
- EXTERIOR FINISHES:**
- GOLDENWOOD - NATURAL PINE - FINGER JOINT EXTERIOR WOOD OR/
  - GOLDENCLAD - AVAILABLE EXTERIOR IN 4 COLOURS: WHITE, BLACK, TAUPE & SABLE (OPTIONAL) OR 30 OPTIONAL EXTERIOR COLOURS
- JAMB EXTENSIONS:**
- GOLDENWOOD - STANDARD JAMB WIDTH 4-9/16"
  - GOLDENCLAD - OVERALL JAMB 5-11/16" (NAIL FIN OPTION)
  - YES - 1" OR 2" (FOR WOOD FRAME ONLY) OR 2" (FOR ALUMINUM CLAD FRAME ONLY) - INCLUDES SILL EXTENSION - INSTALLED TO OUTSIDE
- FEATURES & DETAILS:**
- REFER TO LITERATURE/BROCHURE
- OPERATION:**
- HINGED LEFT (L) OR RIGHT (R) AS VIEWED FROM OUTSIDE
  - OUT SWING OPTION IN SINGLE DOOR ONLY
  - NO OUT SWING OPTION FOR DOUBLE DOORS
- HARDWARE PREP:**
- DRILLED 2 1/8" AND DEADBOLT 1 5/8" ON 5 1/2" CENTRE - SINGLE DOORS
  - DRILLED 2 1/8" AND DEADBOLT 1 5/8" ON 5 1/2" CENTRE ON ACTIVE DOOR AND 2 1/8" FOR DUMMY SET ON FLUSH BOLT DOOR SLAB - DOUBLE DOORS
  - BACK SET 2' 6" AND 2' 8" DOORS - 2 3/8"
  - BACK SET 2' 10" AND 3' 0" DOORS - 2 3/4"
  - JAMB PREPARED FOR STRIKE PLATE
  - 2 1/8" DEADBOLT OR NO DEADBOLT DRILL AVAILABLE AS AN OPTION
- CAUTION:**
- SIDELITES ATTACHED TO DOUBLE DOORS MAKE IT IMPOSSIBLE TO SECURE THE DOOR JAMBS TO FIXED WALL FRAMING MEMBERS. THE RESULT IS OFTEN IMPROPER INSTALLATION. THE SAME IS TRUE WHEN ATTACHING LARGE TRANSOMS OR DECORATIVE SHAPES TO THE TOP OF DOUBLE DOORS. GOLDEN WILL ACCEPT **NO RESPONSIBILITY** FOR IMPROPER OPERATION OF DOUBLE DOORS WITH THESE INSTALLATIONS. ALL DOUBLE DOORS SHOULD HAVE FRAMING BETWEEN SIDELITES AND HEAVY TRANSOMS.