

GOLDENCLAD® & GOLDENWOOD® TERRACE PATIO ENTRY PRODUCT HIGHLIGHTS

PRODUCT SIZE RANGE:

• WIDTHS: 61 5/16" (PE50: 2-2' 6" SLABS), 65 5/16" (PE54: 2-2'8" SLABS), 69 5/16" (PE58:

2-2'10" SLABS), 73 5/16" (PE60: 2-3'0 SLABS)

OR COMBINE WITH SIDELITE PANEL FOR WIDTHS OF 91 1/8" (PE76: 3-2'6"). 97 3/16"

(PE80: 3-2'8"), 103 1/8" (PE86: 3-2'10"), 109 3/16" (PE90: 3-3'0")

STANDARD HEIGHT 81 1/2"

NO CUSTOM SIZING

STANDARD GLAZING:

• TEMPERED INSULATING GLASS WITH WARM EDGE INTERCEPT SPACER - CAN

UPGRADE TO WARM EDGE SUPERSPACER

• POLYPROPYLENE VINYL EXTERIOR AND INTERIOR DOOR LITE SURROUND - CAN

EITHER BE PAINTED OR LEFT WHITE (WILL NOT YELLOW)

• GOLDENGLASS WITH LOW E HARD COATING ON INSIDE (#3 SURFACE) AND ARGON GAS), OBSCURE, BRONZE OR GREY LITE AVAILABLE AS AN OPTION

GRILLES BETWEEN GLASS AND SDL WILL AFFECT ENERGY RATING

GRILLE OPTIONS:

COLONIAL, VICTORIAN, MUSKOKA OR CUSTOM (SDL & GBG ONLY) PATTERNS

• AVAILABLE WITH: 5/8" OR 5/16" INTERNAL FLAT ALUMINUM GRILLE BAR (GBG), 3/4" PROFILED ALUMINUM GEORGIAN GRILLE BAR (GBG), 1" SIMULATED DIVIDED LITE (SDL) OR 2" SIMULATED HORIZONTAL MULLION GRILLE BAR - ASK FOR DETAILS

EXTERIOR FINISHES:

GOLDENWOOD - NATURAL PINE - FINGER JOINT EXTERIOR WOOD OR/

GOLDENCLAD - AVAILABLE EXTERIOR IN 4 COLOURS: WHITE, BLACK, TAUPE

& SABLE (OPTIONAL) OR 30 OPTIONAL EXTERIOR COLOURS

DOOR PANELS:

HEAVY 24 GAUGE STEEL (NOT 26 OR 28 GAUGE) WITH FOAMED URETHANE CORE.

(R13 VALUE) - 13/4" THICK

SCREEN FINISHES:

WHITE ON WHITE CLAD (OR ON WOOD EXTERIOR), MATCHING TAUPE, SABLE AND

BLACK ON CLAD EXTERIORS

JAMB EXTENSIONS:

• GOLDENWOOD - STANDARD JAMB WIDTH 4-9/16"

• GOLDENCLAD - OVERALL JAMB 5 11/16" (NAIL FIN OPTION)

• YES - 1" OR 2" (FOR WOOD FRAME ONLY) OR 2" (FOR ALUMINUM CLAD FRAME

ONLY) - INCLUDES SILL EXTENSION - INSTALLED TO OUTSIDE

FEATURES & DETAILS:

• REFER TO LITERATURE/BROCHURE

OPERATION:

SWINGING INWARD ONLY - SWINGING PANELS WILL BE MULLION HINGLED UNLESS

ASK FOR JAMB HINGED

OPERATION AS VIEWED FROM OUTSIDE

EXAMPLE: 2 WIDE DOOR WITH LEFT DOOR SWINGING INWARD - CODE IS "RF" -

RIGHT HINGED LEFT PANEL, FIXED RIGHT PANEL

HARDWARE PREP

• DRILLED 2 1/8" AND DEADBOLT 1 5/8" ON 5 1/2" CENTRE ON ACTIVE DOOR

• NO PREP ON STATIONARY DOOR PANEL - OPTION IF WANT DUMMY BORE

• BACK SET 2' 6" AND 2' 8" DOORS - 2 3/8"

• BACK SET 2' 10" AND 3' 0" DOORS - 2 3/4"

• JAMB PREPARED FOR STRIKE PLATE

2 1/8" DEADBOLT OR NO DEADBOLT DRILL AVAILABLE AS AN OPTION