

PRODUCT HIGHLIGHTS

February, 2005

GOLDENWOOD / GOLDENCLAD INSULATED ENTRY SYSTEMS

PRODUCT SIZE RANGE :

- SINGLE, SINGLE with SIDELITE(S) and DOUBLE DOOR
- WIDTH 33 ½" to 74"
- STANDARD HEIGHT 81 ½" or 97 ½" HEIGHT OPTIONAL
- OTHER CUSTOM SIZES AVAILABLE

SIDELITES :

- YES – 9 ¾" (NSL) or 15 ½" (SL) FRAME WIDTH – REFER to LITERATURE

DOOR PANELS :

- HEAVY 24 GAUGE STEEL (Not 26 or 28 Gauge) with FOAMED URETHANE CORE (R13 Value) – 1 ¾" THICK

STANDARD GLAZING : (IF APPLICABLE)

- STANDARD CLEAR INSULATING GLASS in HALF LITES AND SIDELITES
- TEMPERED CLEAR INSULATING GLASS in ¾ & FULL LENGTH LITES
- POLYPROPYLENE VINYL EXTERIOR and INTERIOR DOOR LITE SURROUND – Can either be Painted or left White (will not yellow)
- GOLDENGLASS (LOW E / ARGON GAS), OBSCURE, BRONZE or GREYLITE AVAILABLE as an OPTION

GRILLE OPTIONS : (IF APPLICABLE)

- COLONIAL, VICTORIAN or MUSKOKA (SDL & GBG ONLY) PATTERNS in ;
1" REMOVABLE WOOD PROFILED BOTH SIDES with FULL SURROUND,
5/8" or 5/16" INTERNAL FLAT ALUMINUM GRILLE BAR (G.B.G.), ¾"
PROFILED ALUMINUM GEORGIAN GRILLE BAR (G.B.G.) OR 1"
SIMULATED DIVIDED LITE (SDL) – ASK FOR DETAILS

DECORATIVE LITE OPTIONS :

- REFER TO DECORATIVE DOOR LITE LITERATURE FOR GLAZING and CAMING OPTIONS

EXTERIOR FINISHES :

- GOLDENWOOD – NATURAL PINE – FINGER JOINT EXTERIOR WOOD OR
- GOLDENCLAD – ALUMINUM CLAD FRAME EXTERIOR IN 6 COLOURS :

A - ALMOND
T - TAUPE

S - SABLE
W - WHITE

G - GREEN
C - CRANBERRY (OPTIONAL)

JAMB EXTENSIONS :

- GOLDENWOOD – STANDARD JAMB WIDTH 4 9/16"
- GOLDENCLAD – OVERALL JAMB 5 11/16" (NAIL FIN OPTION)
- YES – 1" or 2" (FOR WOOD FRAME ONLY) or 2" (FOR ALUM. CLAD FRAME ONLY) - INCLUDES SILL EXTENSION – INSTALLED TO OUTSIDE

FEATURES & DETAILS :

- REFER TO LITERATURE / BROCHURES

OPERATION :

- HINGED LEFT (L) or RIGHT (R) as VIEWED FROM OUTSIDE
- OUTSWING OPTION in SINGLE DOOR ONLY
- NO OUTSWING OPTION for DOUBLE DOORS

HARDWARE PREP. :

- DRILLED 2 1/8" and DEADBOLT 1 5/8" on 5 ½" CENTRE – Single Doors
- DRILLED 2 1/8" and DEADBOLT 1 5/8" on 5 ½" CENTRE on ACTIVE DOOR and 2 1/8" for DUMMY SET on FLUSH BOLT DOOR SLAB – Double Doors
- BACKSET 2'6" and 2'8" DOORS – 2 3/8"
BACKSET 2'10" and 3'0" DOORS – 2 ¾"
- JAMB PREPARED for STRIKE PLATE
- 2 1/8" DEADBOLT or NO DEADBOLT DRILL AVAILABLE as an OPTION

CAUTION :

- SIDELITES ATTACHED TO DOUBLE DOORS MAKE IT IMPOSSIBLE TO SECURE THE DOOR JAMBS TO FIXED WALL FRAMING MEMBERS. THE RESULT IS OFTEN IMPROPER INSTALLATION. THE SAME IS TRUE WHEN ATTACHING LARGE TRANSOMS OR DECORATIVE SHAPES TO THE TOP OF DOUBLE DOORS. GOLDEN WILL ACCEPT NO RESPONSIBILITY FOR IMPROPER OPERATION OF DOUBLE DOORS WITH THESE INSTALLATIONS. ALL DOUBLE DOORS SHOULD HAVE FRAMING BETWEEN SIDELITES AND HEAVY TRANSOMS.

