

GOLDENCLAD®


ALUMINUM CLAD WINDOWS, ENTRIES AND PATIO DOORS

GOLDENWOOD®

ALL WOOD WINDOWS, ENTRIES AND PATIO DOORS







STANDARD COLOURS















GoldenWood Natural Pine (unfinished)

OPTIONAL COLOURS



HARDWARE OPTIONS (may vary by product)



White





Black



Antique Brass





Brushed Nickel

COLOUR NOTES

- GoldenWood products feature a wood exterior.
- Window interiors are available primed.
- Colour and grain variations are natural characteristics of wood.
- Due to printing limitations, the colours shown on this page may differ from actual colours. Please contact us for exact colour and finish samples.

GRILLE PATTERNS



OPTIONAL ACCESSORIES






1 1/2" Clad Brickmould 2" Standard Wood Brickmould

GRILLE OPTIONS



CASEMENT & AWNING WINDOWS





For increased energy efficiency, GoldenGlass® offers Low E glass and argon filling as standard.

Warm Edge Technology combined with Intercept $^{\text{\tiny M}}$ spacer increases the thermal performance. Consider using our Superspacer $^{\text{\tiny B}}$ option to further reduce the U-value and increase energy ratings.

The beauty and warmth of straight-grained pine offers the choice of painted or stained interiors. Alternate species available upon request.

Standard multipoint locking hardware offers exceptional operation with a single lever for ease of use.

Low-maintenance extruded aluminum cladding offers a weather resistant, beautiful exterior finish.

Operating and fixed units have a common interior and exterior appearance for aesthetic uniformity.

SIZES

GoldenClad and GoldenWood casement and awning windows are available in a wide range of standard and custom sizes that will meet most new construction and renovation requirements.

Exact Frame Size	Width (min - max)	Height (min - max)
Casement	15 3/4" - 35 7/16" 400mm - 900mm	18 1/2" - 76 3/4" 470mm - 1950mm
Fixed Casement	15 3/4" - 70 7/8" 400mm - 1800mm	15 3/4" - 76 3/4" 400mm - 1950mm
Awning	15 3/4" - 55 1/8" 400mm - 1400mm	18 1/2" - 47 1/4" 470mm - 1200mm

Please reference the Sizes & Shapes section of the window product page available at www.goldenwindows.com for detailed information regarding rough opening, exact frame sizes, glass size and sizing limitations.

OPTIONS

Select from 6 standard, 30 optional or unlimited custom colours.

Available in GoldenWood with a natural pine exterior.

Multiple grille options including grilles between glass, removable wood grilles and simulated divided lights (SDL).

Choose from Colonial, Victorian, Muskoka and Custom grille patterns.

 ${\tt 3}$ standard and ${\tt 3}$ optional hardware finishes to choose from.

Exterior brickmould and sill nosing are available.

White, coppertone, black or wood grain screens available.

HARDWARE



Various Encore™ hardware finishes are available to match any decor.

PERFORMANCE

CLAD/WOOD CASEMENT/AWNING WINDOW (OPERATING)

Class CW-PG40: Size tested 900 x 1950 mm (35.4 x 76.8)-Type C Positive Design Pressure = 2130 Pa (44 psf) Negative Design Pressure = -2130 Pa (-44 psf) Water Penetration Resistance Test Pressure = 400 Pa (8 psf) Canadian Air Infiltration/Exfiltration = A3 Level (0.297/0.239m³/h/m)

CLAD/WOOD CASEMENT/AWNING WINDOW (FIXED)

Class CW-PG35: Size tested 2000 x 2000 mm (78.7 x 78.7)-Type FW Positive Design Pressure = 1760 Pa (37 psf)
Negative Design Pressure = -1760 Pa (-37 psf)
Water Penetration Resistance Test Pressure = 730 Pa (15 psf)
Canadian Air Infiltration/Exfiltration = Fixed Level (0.097/0.044m³/h/m)

DOUBLE HUNG WINDOWS





For increased energy efficiency, GoldenGlass® offers Low E glass and argon filling as standard.

Warm Edge Technology combined with Intercept™ spacer increases the thermal performance. Consider using our Superspacer® option to further reduce the U-value and increase energy ratings.

Constant force balances are concealed in a stationary jamb liner. Experience ease-of-operation as a result of no side pressure.

The beauty and warmth of straight-grained pine offers the choice of painted or stained interiors. Alternate species available upon request.

Cam action lock with security release button and thumb release latches for effortless tilting and removal of sashes.

Foam compression weatherstripping at all critical points for year-round comfort.

Low-maintenance extruded aluminum cladding offers a weather resistant, beautiful exterior finish.

SIZES

GoldenClad and GoldenWood double hung windows are available in a wide range of standard and custom sizes that will meet most new construction and renovation requirements.

Exact Frame Size	Width (min - max)	Height (min - max)
Double Hung	16 15/16" - 47 1/4" 430mm - 1200mm	29 5/8" - 76 3/4" 752mm - 1950mm
Double Hung Transom	16 15/16" - 70 7/8" 430mm - 1800mm	15 11/16" - 47 1/4" 398mm - 1200mm
Double Hung Picture	16 15/16" - 70 7/8" 430mm - 1800mm	29 5/8" - 76 3/4" 752mm - 1950mm

^{*}If width is less than 23 5/8", maximum height is 70 7/8".

Please reference the Sizes & Shapes section of the window product page available at www.goldenwindows.com for detailed information regarding rough opening, exact frame sizes, glass size and sizing limitations.

OPTIONS

Select from 6 standard, 30 optional or unlimited custom colours.

Available in GoldenWood with a natural pine exterior.

Multiple grille options including grilles between glass, removable wood grilles and simulated divided lights (SDL).

Choose from Colonial, Victorian, Muskoka and Custom grille patterns.

3 standard and 3 optional hardware finishes to choose from. Optional sash lifts are available.

Jamb liners available in white, grey or a split colour to match the exterior colour of the window with an optional interior wood jamb liner insert.

Exterior brickmould and sill nosing are available.

Cottage style available with a smaller upper sash and a larger lower sash with an optional interior wood jamb liner insert.

HARDWARE



White (Standard)



Oil-Rubbed Bronze



Coppertone (Standard)



Antique Brass



Black (Standard)



Brushed Nickel

PERFORMANCE

CLAD/WOOD DOUBLE HUNG WINDOW


Class LC-PG35: Size tested 1159 x 2360 mm (45.6 x 92.9)-Type H Positive Design Pressure = 1710 Pa (36 psf) Negative Design Pressure = -1710 Pa (-36 psf) Water Penetration Resistance Test Pressure = 400 Pa (8 psf) Canadian Air Infiltration/Exfiltration = A3 Level (0.230/0.410m³/h/m)

CLAD/WOOD DOUBLE HUNG FIXED PICTURE WINDOW

Class CW-PG35: Size tested 2000 x 2360 mm (78.7 x 92.9)-Type FW Positive Design Pressure = 3930 Pa (82 psf)
Negative Design Pressure = -3930 Pa (-82 psf)
Water Penetration Resistance Test Pressure = 730 Pa (15 psf)
Canadian Air Infiltration/Exfiltration = Fixed Level (0.291/0.201m³/h/m)

PICTURE & ARCHITECTURAL WINDOWS






For increased energy efficiency, GoldenGlass® offers Low E glass and argon filling as standard.

Warm Edge Technology combined with Intercept $^{\text{\tiny M}}$ spacer increases the thermal performance. Consider using our Superspacer $^{\text{\tiny B}}$ option to further reduce the U-value and increase energy ratings.

Low-maintenance extruded aluminum cladding offers a weather resistant, beautiful exterior finish.

Natural unfinished pine will add warmth to the interior of any home. Alternate species available upon request.

SHAPES



SIZES

GoldenClad and GoldenWood picture and architectural windows are available in a wide range of standard and custom sizes that will meet most new construction and renovation requirements.

Exact Frame Size	Width (min - max)	Height (min - max)
Rectangle	4" - 110 1/4" 100mm - 2800mm	4" - 110 1/4" 100mm - 2800mm
Half Round	19 11/16" - 110 1/4" 500mm - 2800mm	9 13/16" - 55 1/8" 250mm - 1400mm
Elliptical	47 1/4" - 110 1/4" 1200mm - 2800mm	11 13/16" - 27 9/16" 300mm - 700mm

^{*}Maximum square footage of actual frame size cannot exceed 50 ft² or 4.64m².

Please reference Sizes & Shapes section of the window product page available at www.goldenwindows.com for detailed information regarding rough opening, exact frame sizes, glass size and sizing limitations.

OPTIONS

Select from 6 standard, 30 optional or unlimited custom colours.

Available in GoldenWood with a natural pine exterior.

Multiple grille options including grilles between glass, removable wood grilles and simulated divided lights (SDL).

Choose from Colonial, Victorian, Muskoka and Custom grille patterns.

Exterior brickmould and sill nosing are available.

PERFORMANCE

CLAD/WOOD FIXED PICTURE WINDOW

Class CW-PG35: Size tested 1600 x 3200 mm (63 x 126.0)-Type FW Positive Design Pressure = 3870 Pa (81 psf)
Negative Design Pressure = -3870 Pa (-81 psf)
Water Penetration Resistance Test Pressure = 730 Pa (15 psf)
Canadian Air Infiltration/Exfiltration = Fixed Level (0.232/0.174m³/h/m)

SLIDING PATIO DOORS





Engineered wood featuring a durable structural core that ensures your sliding patio door will last a long time.

The multipoint locking system adds safety and reliability using premium handle sets that feature a contour shape which is both elegant and easy to grasp.

Permanently lubricated tandem rollers to ensure a smooth gliding door on a stainless steel track.

A continuous plane of weatherstripping results in a tight seal, reducing air infiltration and improving the overall energy efficiency.

The screen features a full height integrated pull handle with four separate ball bearing, fully adjustable, plated steel roller mechanisms for smooth operation (not shown).

*Sliding door image is a display model and not indicative of final proportions.

OPTIONS

Available in both the traditional (wide rail) and the contemporary (narrow rail) designs.

Select from 6 standard, 30 optional or unlimited custom colours.

2 standard and 6 optional hardware finishes to choose from.

Available in GoldenWood with a natural pine exterior.

Multiple grille options including grilles between glass, removable wood grilles and simulated divided lights (SDL).

Choose from Colonial, Victorian, Muskoka and Custom grille patterns.

Available in both the traditional (wide rail) and the contemporary (narrow rail) designs.

Optional security bar, foot bolt and keyed-lock assembly.

HARDWARE



SIZES

GoldenClad and GoldenWood sliding patio doors are available in a wide range of standard and custom sizes that will meet most new construction and renovation requirements.

Standard Double Sliding Door (OX or XO) Widths	59" (1498mm), 70 15/16" (1802mm), 95" (2412mm)
Standard Quad Sliding Door (OXXO) Widths	117 13/16" (2992mm), 141 3/4" (3600mm), 189 3/4" (4820mm)
Standard Heights	79 3/8" (2016mm), 82 3/8" (2093mm), 95 3/8" (2423mm)

^{*}Custom sizes available upon request.

Please reference the Sizes & Shapes section of the window product page available at www.goldenwindows.com for detailed information regarding rough opening, exact frame sizes, glass size and sizing limitations.

PERFORMANCE

CLAD/WOOD SLIDING PATIO DOOR

Class LC-PG30: Size tested 2412 x 2423 mm (94.96 x 95.39)-Type SD

Positive Design Pressure = 1440 Pa (30 psf)

Negative Design Pressure = -1440 Pa (-30 psf) Water Penetration Resistance Test Pressure = 400 Pa (8 psf)

Canadian Air Infiltration/Exfiltration = A3 Level (0.892/0.921m3/h/m)

CLAD/WOOD SLIDING PATIO DOOR SIDELITE

Class LC-PG30: Size tested 1251 x 2423 mm (49.25 x 95.39)-Type SLT Positive Design Pressure = 1440 Pa (30 psf) Negative Design Pressure = -1440 Pa (-30 psf) Water Penetration Resistance Test Pressure = 510 Pa (11 psf)

voter Penetration Resistance Test Pressure = 510 Pa (11 pst)
Canadian Air Infiltration/Exfiltration = A3 Level (0.443/0.433m³/h/m)



GOLDENWINDOWS

In 1961, Golden Windows began as a small Kitchener millwork plant with only a handful of employees under the name Golden Triangle Windows. Over the five decades the company has been in operation, much has changed, both in consumer taste and window innovation, but it remains a family owned and operated organization. By focusing on the needs and desires of our customers, the business has continued to grow and expand. Golden Windows is now an integrated designer, manufacturer and distributor of quality windows and doors servicing Ontario, portions of the United States and other countries such as the Cayman Islands, Great Britain and Japan.

Golden Windows is a reliable source for high quality products manufactured at our facility in Kitchener, Ontario. We combine a highly skilled, craftsman oriented workforce with the latest technology to produce aluminum, wood and vinyl windows and doors that exceed your need for energy efficiency, natural air flow and easy cleaning and maintenance. This is done by partnering with our suppliers and quality builders, renovators and dealers to satisfy your every need.

By being one of only a few window and door companies that have obtained the ISO 9001 designation, we are able to consistently provide exceptional lead times and on-time delivery of these superior products. By believing in a philosophy of continuous improvement, our products have been designed to provide you with trouble-free performance. We are confident that you will enjoy your Golden Windows for many years to come.

Golden Windows has retail locations in Kitchener, London and Kanata. Our products are also available through quality builders, renovators and dealers.

KANATA SHOWROOM

1112 March Road, Kanata ON K2W 1B9 Phone: 613-592-9111 Fax: 613-592-0888

KITCHENER HEAD OFFICE AND SHOWROOM

888 Guelph Street, Kitchener ON N2H 5Z6 Phone: 519-579-3810 or 1-800-265-2290 Fax: 519-579-8900

LONDON SHOWROOM

309 Exeter Road, London ON N6L 1C1 Phone:519-652-1677 Fax: 519-652-9110





