

PRODUCT HIGHLITES

February, 2005

GOLDENWOOD / GOLDENCLAD SWINGING PATIO ENTRY

PRODUCT SIZE RANGE :

- WIDTHS : 61 5/16" (PE50 : 2-2'6" slabs) , 65 5/16" (PE54 : 2-2'8" slabs) , 69 5/16" (PE 58 : 2-2'10" slabs) , 73 5/16" (PE60 : 2-3'0" slabs)
- OR COMBINE with SIDELITE PANEL for WIDTHS of 91 1/8" (PE76 : 3-2'6") , 97 3/16" (PE80 : 3-2'8") , 103 1/8" (PE86 : 3-2'10") , 109 3/16" (PE90 : 3-3'0")
- HEIGHT 81 1/2"
- NO CUSTOM SIZING

GRILLE OPTIONS :

- COLONIAL, VICTORIAN or MUSKOKA (SDL & GBG ONLY) PATTERNS in :
- 1" REMOVABLE WOOD PROFILED BOTH SIDES WITH FULL SURROUND
- 5/8" FLAT ALUMINUM BAR in WHITE, ALMOND, TAUPE, GREEN, SABLE and TAUPE/WHITE and 5/16" NARROW BRASS and PEWTER SEALED WITHIN INSUL GLASS (G.B.G) – will affect energy rating
- 3/4" PROFILED ALUMINUM GEORGIAN BAR IN WHITE, ALMOND, TAUPE, GREEN, SABLE and TAUPE/WHITE WITHIN INSUL GLASS (G.B.G) – will affect energy rating
- 1" SIMULATED DIVIDED LITES (SDL) – ALUMINUM ON ALL EXTERIORS – WOOD INTERIORS. (will affect energy rating)
- 2" SIMULATED HORIZONTAL MULLION GRILLE BAR (Alum. Ext./Wood Int.)

GLAZING OPTIONS :

- TEMPERED INSULATING GLASS with WARM EDGE " INTERCEPT " SPACER (Can Upgrade to Warm Edge "SuperSpacer")
- POLYPROPYLENE VINYL EXTERIOR and INTERIOR DOOR LITE SURROUND – Can either be Painted or left White (will not yellow)
- OR BRONZE or GREYLITE REPLACES OUTSIDE LITE OF GLASS
- OR GOLDENGLASS (highly recommended) WITH "LOW E" HARD COATING ON INSIDE LITE OF GLASS (#3 surface) + ARGON GAS ENHANCED AIR SPACE (grilles between glass and SDL will affect energy rating)

EXTERIOR FINISHES :

- GOLDENWOOD – NATURAL PINE – FINGER JOINT EXTERIOR WOOD OR
- GOLDENCLAD – ALUMINUM CLAD FRAME EXTERIOR IN 6 COLOURS :

A - ALMOND
T - TAUPE

S - SABLE
W - WHITE

G - GREEN
C - CRANBERRY (OPTIONAL)

DOOR PANELS :

- HEAVY 24 GAUGE STEEL (Not 26 or 28 Gauge) with FOAMED URETHANE CORE (R13 Value) – 1 3/4" THICK

SCREEN FINISHES :

- WHITE on WHITE CLAD (or on WOOD EXTERIOR), MATCHING ALMOND, CRANBERRY, GREEN, SABLE and TAUPE on CLAD EXTERIORS.

JAMB EXTENSIONS :

- GOLDENWOOD – STANDARD JAMB WIDTH 4 9/16"
- GOLDENCLAD – OVERALL JAMB 5 11/16" (NAIL FIN OPTION)
- YES – 1" or 2" (FOR WOOD FRAME ONLY) OR 2" (FOR ALUM. CLAD FRAME ONLY) – INCLUDES SILL EXTENSION - INSTALLED TO OUTSIDE

FEATURES & DETAILS :

- REFER TO LITERATURE / BROCHURES

OPERATION :

- SWINGING INWARD ONLY – SWINGING PANELS will be MULLION HINGED UNLESS ASK for JAMB HINGED
- OPERATION AS VIEWED FROM OUTSIDE
- EXAMPLE : 2 WIDE DOOR with LEFT DOOR SWINGING INWARD – CODE is " RF " – RIGHT HINGED LEFT PANEL, FIXED RIGHT PANEL

HARDWARE PREP. :

- DRILLED 2 1/8" and DEADBOLT 1 5/8" on 5 1/2" CENTRE on ACTIVE DOOR
- NO PREP ON STATIONARY DOOR PANEL – Option if Want Dummy Bore
- BACKSET 2'6" and 2'8" DOORS – 2 3/8"
BACKSET 2'10" and 3'0" DOORS – 2 3/4"
- JAMB PREPARED for STRIKE PLATE
- 2 1/8" DEADBOLT or NO DEADBOLT DRILL AVAILABLE as an OPTION

